



COMPATIBILITY LIST - Energy Meter

Overview of all models.
Additional models can be tested for compatibility upon request.

Brand - Model	Status	Modbus - TCP	Modbus - RTU	Gateway / Interface	Measurement	Max-Speed RTU / kbit/s	Note
IME							
CE4DF3DTMID	●	TCP*	RTU	SXIIP	Direct	38400 kbit/s	*TCP mode requires the TCP/RTU gateway – RTU only with CB 2.0
CE4TBDTMID	●	TCP*	RTU	SXIIP	Direct	38400 kbit/s	*TCP mode requires the TCP/RTU gateway – RTU only with CB 2.0
CE6DMID56	●	TCP*	RTU	SXIIP	Direct	19200 kbit/s	*TCP mode requires the TCP/RTU gateway – RTU only with CB 2.0
MF961ORFCDT	●	TCP	RTU	-	Indirect	38400 kbit/s	-
JANITZA							
UMG 604-PRO	●	TCP	not supported	-	-	-	-
UMG 104	●	TCP	not supported	-	-	-	-
UMG 96 RM	●	TCP	RTU	-	Indirect	115200 kbit/s	-
SIEMENS							
PAC 2200	●	TCP	not supported	-	Indirect	-	-
Circutor							
Circutor - CVM-E3-MINI-ITF-485-IC	●	not supported	RTU	-	Indirect	115200 kbit/s	- Available from sw_Version > 260422.1500

Glossary

Status

● More than 30 units in operation, stable performance