



COMPATIBILITY LIST - Energy Meter

Overview of all models.
Additional models can be tested for compatibility upon request.

Brand - Model		Status	Modbus - TCP	Modbus - RTU	Gateway / Interface	Measurement	Max-Speed RTU / kbit / s	Note
IME								
CE4DF3DTMID		●	TCP*	RTU	SXIIP	Direct	38400 kbit / s	*TCP mode requires the TCP / RTU gateway – RTU only with CB 2.0
CE4TBDTMID		●	TCP*	RTU	SXIIP	Direct	38400 kbit / s	*TCP mode requires the TCP / RTU gateway – RTU only with CB 2.0
CE6DMID56		●	TCP*	RTU	SXIIP	Direct	19200 kbit / s	*TCP mode requires the TCP / RTU gateway – RTU only with CB 2.0
MF961ORFCDT		●	TCP	RTU	-	Indirect	38400 kbit / s	-
JANITZA								
UMG 604-PRO		●	TCP	not supported	-	Direct-Indirect	-	-
UMG 104		●	not supported	RTU	-	Indirect	921600 kbit / s	-
UMG 96 RM		●	TCP	RTU	-	Indirect	115200 kbit / s	-
SIEMENS								
PAC 2200		●	TCP	not supported	-	Indirect	-	-
Circutor								
Circutor - CVM-E3-MINI-ITF-485-IC		●	not supported	RTU	-	Indirect	115200 kbit / s	- Available from sw_Version > 260422.1500

Glossary

Status
● More than 30 units in operation, stable performance